




#### Dimensions

Product dimensions (mm)	ø210 x 220
Net weight (g)	2638
Gross weight (Kg)	2,9
Drilling hole (mm)	179

#### Scheme



#### Scheme



### Inground luminaire from the TROLL family Atlante.

#### DESCRIPTION

Inground luminaire from the TROLL family Atlante setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as architectural lighting of semi-covered spaces and façades. Designed for inground installation. Body built in die-cast aluminium with the frontal made of tempered glass and stainless steel finished in Polish steel. Luminaire is IP67 and IK07. Luminaire built-in an high efficiency faceted reflector made of high purity aluminium with an angle beam of 10°. Luminaire sets a 12 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 1727 Lm, with an efficiency of 95,9 Lm/W and a total consumption of 18 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.5203.0032.20
Product type	OUT
Category	Recessed
Family	Atlante
Subfamily	Atlante
Materials	Body built in die-cast aluminium with the frontal made of tempered glass and stainless steel.
Optical system	Luminaire built-in a high efficiency faceted reflector made of high purity aluminium.
Installation instructions	Luminaire designed for inground installation.
Pictograms	 

#### Product

Real power (W)	18
Real luminous flux (Lm)	1727
Luminous efficiency (Lm/W)	95,9
Beam angle (°)	12
Life time (h)	50000
IP	67
IK	10
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Stainless steel
Energy efficiency class	A+

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,99

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	16
Nominal luminous flux (Lm)	1986
Colour temperature (K)	3000
CRI	80

#### Photometry

Photometry

