




Dimensions

Product dimensions (mm) Ø264 x 105

Scheme

Scheme



Product

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 10                 |
| Real luminous flux (Lm)     | 201                |
| Luminous efficiency (Lm/W)  | 20,1               |
| Beam angle (°)              | 105                |
| Life time (h)               | 50000              |
| IP                          | 54                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..230V, 50/60Hz |
| Colour                      | Anthracite         |
| Energy efficiency class     | A                  |

Control gear


|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |
| Factor de potencia    | 0,9                     |

Light source

|                            |      |
|----------------------------|------|
| Light source included      | Yes  |
| Light source               | Led  |
| Nominal power (W)          | 9    |
| Nominal luminous flux (Lm) | 450  |
| Colour temperature (K)     | 3000 |
| CRI                        | 80   |

Photometry

Photometry



Outdoor sconce from the TROLL family Apliques.

DESCRIPTION

Outdoor sconce from the TROLL family Apliques setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general lighting of passing areas, entrances, staircases or similar areas. Designed for wall surface mounted. Luminaire body built in die-cast aluminium finished in anthracite. Luminaire is IP54. Luminaire built-in an opal diffuser that could be complemented with antiglare louver with an angle beam of 105°. Luminaire sets a 10 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 201 Lm, with an efficiency of 20,1 Lm/W and a total consumption of 10 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

|                           |   |
|---------------------------|---|
| Item code                 | 11.6105.0003.22   |
| Product type              | OUT   |
| Category                  | Surface   |
| Family                    | Apliques  |
| Subfamily                 | Apliques  |
| Materials                 | Luminaire body built in die-cast aluminium.   |
| Optical system            | Luminaire built-in an opal diffuser that could be complemented with antiglare louver. |
| Installation instructions | Luminaire designed for wall surface mounted.  |

Pictograms

