




**Dimensions**

Product dimensions (mm) 57 x 210 x 130

**Scheme**

**Scheme**



**Product**

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 7                  |
| Real luminous flux (Lm)     | 148                |
| Luminous efficiency (Lm/W)  | 21,1               |
| Beam angle (°)              | 105                |
| Life time (h)               | 50000              |
| IP                          | 54                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..230V, 50/60Hz |
| Colour                      | Anthracite         |
| Energy efficiency class     | A                  |

**Control gear**


|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |
| Factor de potencia    | 0,9                     |

**Light source**

|                            |      |
|----------------------------|------|
| Light source included      | Yes  |
| Light source               | Led  |
| Nominal power (W)          | 6,3  |
| Nominal luminous flux (Lm) | 300  |
| Colour temperature (K)     | 3000 |
| CRI                        | 80   |

**Photometry**

**Photometry**



**Outdoor sconce from the TROLL family Apliques.**

**DESCRIPTION**

Outdoor sconce from the TROLL family Apliques setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general lighting of passing areas, entrances, staircases or similar areas. Designed for wall surface mounted. Luminaire body built in die-cast aluminium finished in anthracite. Luminaire is IP54. Luminaire built-in an opal diffuser that could be complemented with antiglare louver with an angle beam of 105°. Luminaire sets a 7 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 148 Lm, with an efficiency of 21,1 Lm/W and a total consumption of 7 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

|                           |                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------|
| Item code                 | 11.6105.0013.22                                                                       |
| Product type              | OUT                                                                                   |
| Category                  | Surface                                                                               |
| Family                    | Apliques                                                                              |
| Subfamily                 | Apliques                                                                              |
| Materials                 | Luminaire body built in die-cast aluminium.                                           |
| Optical system            | Luminaire built-in an opal diffuser that could be complemented with antiglare louver. |
| Installation instructions | Luminaire designed for wall surface mounted.                                          |

**Pictograms**

