


Dimensions

Product dimensions (mm)	ø250
Packing dimensions (mm)	245 x 245 x 245

Scheme

Scheme



Product

Real power (W)	20
Real luminous flux (Lm)	2700
Luminous efficiency (Lm/W)	135
Beam angle (°)	120
Life time (h)	50000
IP	65
IK	8
Electrical class insulation	Class 1
Operating temperature	from -20°C to 40°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey
Energy efficiency class	A++

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,98

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	18
Nominal luminous flux (Lm)	3000
Average life time (h)	50000
Colour temperature (K)	4000
Current (mA)	500
Colour consistency (SDCM)	3
CRI	80

Accesorios

20/6604/21 For ref: 6604/20, 6604/60.

Architectural luminaire from the TROLL family Riddle.

DESCRIPTION

Architectural luminaire from the TROLL family Riddle setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for floor wall or ceiling surface mounted. Body built in die-cast aluminium and polycarbonate finished in grey. Luminaire is IP65. Luminaire built-in a Polycarbonate opal diffuser with an angle beam of light & shadows effect. Luminaire sets a 18 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a total consumption of 20 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.6604.1084.21
Product type	OUT
Category	Surface
Family	Riddle
Subfamily	Riddle
Materials	Body built in die-cast aluminium and polycarbonate.
Optical system	Luminaire built-in a Polycarbonate opal diffuser.
Installation instructions	Luminaire designed for floor wall or ceiling surface mounted.
Pictograms	

