


**Dimensions**

Product dimensions (mm)	Ø182 x 259
Packing dimensions (mm)	260 x 260 x 355
Net weight (g)	2600
Gross weight (Kg)	3,4

**Scheme****Scheme**

## Industrial highbay luminaire from the TROLL family Campana.

**DESCRIPTION**

Industrial highbay luminaire from the TROLL family Campana setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general lighting of warehouses, supermarkets, exhibition pavilions and other indoor industrial areas. Designed for Ceiling suspended installation. Body built in die-cast aluminium and polycarbonate finished in grey. Luminaire is IP65. Luminaire built-in an diffuser made of synthetic material with an angle beam of 120°. Luminaire sets a 80 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 8100 Lm, with an efficiency of 101,3 Lm/W and a total consumption of 80 W. The average life for the luminaire is 35000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	5010/L184/21
Product type	IN
Category	Industrial
Family	Highbays
Subfamily	Campana
Materials	Body built in die-cast aluminium and polycarbonate.
Optical system	Luminaire built-in a diffuser made of synthetic material.
Installation instructions	Luminaire designed for Ceiling suspended installation.

**Pictograms****Product**

Real power (W)	80
Real luminous flux (Lm)	8100
Luminous efficiency (Lm/W)	101,3
Beam angle (°)	110
Life time (h)	35000
IP	44
Electrical class insulation	Class 1
Operating temperature	from -20°C to 40°C
Electrical feeding	100..240V, 50/60Hz
Colour	Grey
Energy efficiency class	A+

**Control gear**


Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,99

**Light source**

Light source	Led
Nominal power (W)	72
Nominal luminous flux (Lm)	8000
Average life time (h)	35000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

**Photometry**

Photometry



Accessories

5010/60/21	Reflector 60°.
5010/90/21	Reflector 90°.

Scheme

