
**Dimensions**

Product dimensions (mm)	100 X 100 X 70
Net weight (g)	404
Gross weight (Kg)	0,60

Scheme**Scheme****Product**

Real power (W)	6
Real luminous flux (Lm)	303
Luminous efficiency (Lm/W)	50,5
Life time (h)	50000
IP	20
IK	6
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	110..240V, 50/60Hz
Colour	White
Energy efficiency class	A

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,9

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	5,4
Nominal luminous flux (Lm)	394
Colour temperature (K)	3000
Colour consistency (SDCM)	3
CRI	80

Photometry**Decorative minimalist sconce from the TROLL family Doupled.****DESCRIPTION**

Decorative minimalist sconce from the TROLL family Doupled setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as architectural lighting of walls and decorative indoor structures. Designed for wall surface mounted. Luminaire body built in die-cast aluminium finished in white. Luminaire built-in an indirect light optical system with an angle beam of 120°. Luminaire sets a 6 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 303 Lm, with an efficiency of 50,5 Lm/W and a total consumption of 6 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	6310/L/33
Product type	IN
Category	Apliques
Family	Apliques
Subfamily	Doupled
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in an indirect light optical system.
Installation instructions	Luminaire designed for wall surface mounted.

Pictograms

Photometry

