


Dimensions

| | |
|-------------------------|-----------------|
| Product dimensions (mm) | ø500 |
| Packing dimensions (mm) | 505 x 505 x 505 |
| Net weight (g) | 6000 |
| Gross weight (Kg) | 6,3 |

Scheme

Scheme



Architectural luminaire from the TROLL family Riddle S.

DESCRIPTION

Architectural luminaire from the TROLL family Riddle S optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for Ceiling suspended installation. Luminaire body built in die-cast aluminium finished in grey. Luminaire Built-in a matt diffuser with an angle beam of floor washer. Use QT-32 of Max. 100 W lightsource. Lamp not included. Luminaire Built in a ON/OFF fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|--|
| Item code | 6600S/100/21 |
| Product type | OUT |
| Category | Surface |
| Family | Riddle |
| Subfamily | Riddle S |
| Materials | Luminaire body built in die-cast aluminium. |
| Optical system | Luminaire built-in a matt diffuser. |
| Installation instructions | Luminaire designed for Ceiling suspended installation. |

Pictograms



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | Max. 100 |
| IP | 65 |
| IK | 8 |
| Electrical class insulation | Class 1 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Grey |
| Energy efficiency class | D |

Control gear

| | |
|--------------|--------------|
| Control gear | Without Gear |
|--------------|--------------|

Light source

| | |
|----------------------------|--------------------------------|
| Light source | Halogen or retrofit equivalent |
| Lamp holder | E27 |
| Nominal power (W) | 100 |
| Nominal luminous flux (Lm) | 1800 |
| Average life time (h) | 1500 |
| Voltage (V) | 230 |
| Diameter (mm) | 32 |
| Lamp | QT32 |