


---

**Dimensions**


---

Product dimensions (mm)	1200 x 1200 x 3500
-------------------------	--------------------

---



---

**Scheme**



---



---

**Scheme**


---




---

**Product**


---

Real power (W)	326
Beam angle (°)	120
IP	65
IK	10
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey
Energy efficiency class	A

---



---

**Control gear**


---

Control gear included	Yes
Control gear	Electronic Control Gear

---



---

**Light source**


---

Light source	Discharge
Lamp holder	G12
Nominal power (W)	300
Nominal luminous flux (Lm)	13600
Average life time (h)	6000
Voltage (V)	220
Diameter (mm)	25
Lamp	HIT x 2

---



---

**Architectural luminaire from the TROLL family Riddle.**


---



---

**DESCRIPTION**


---

Architectural luminaire from the TROLL family Riddle optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for pole installed. Luminaire body built in die-cast aluminium finished in grey. Luminaire Built-in a matt diffuser with an angle beam of. Luminaire is IP65 and IK10. Use HIT-T of 326 W lightsource. Lamp not included. Luminaire Built in a ON/OFF fed at 220-240V; 50/60 Hz.

Item code	6602/300/21
Product type	OUT
Category	Poles
Family	Riddle
Subfamily	Riddle
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a matt diffuser.
Installation instructions	Luminaire designed for pole installed.

---

**Pictograms**


---

