



Dimensions

| | |
|-------------------------|-----------------|
| Product dimensions (mm) | ø250 |
| Packing dimensions (mm) | 245 x 245 x 245 |
| Net weight (g) | 2900 |
| Gross weight (Kg) | 3,2 |

Scheme

Scheme



Architectural luminaire from the TROLL family Riddle S.

DESCRIPTION

Architectural luminaire from the TROLL family Riddle S optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for wall or ceiling surface mounted as well as hanging. Luminaire body built in die-cast aluminium finished in grey. Luminaire Built-in a matt diffuser with an angle beam of floor washer. Use a 20 W HIT-TC-CE lightsource included with colour temperature 3000° K (warm white). Luminaire Built in a ON/OFF fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|--|
| Item code | 6604/20/21 |
| Product type | OUT |
| Category | Surface |
| Family | Riddle |
| Subfamily | Riddle S |
| Materials | Luminaire body built in die-cast aluminium. |
| Optical system | Luminaire built-in a matt diffuser. |
| Installation instructions | Luminaire designed for wall or ceiling surface mounted as well as hanging. |

Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 22 |
| IP | 65 |
| IK | 8 |
| Electrical class insulation | Class 1 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Grey |
| Energy efficiency class | A |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|-----------|
| Light source included | Yes |
| Light source | Discharge |
| Lamp holder | PGJ5 |
| Nominal power (W) | 20 |
| Nominal luminous flux (Lm) | 1650 |
| Average life time (h) | 5000 |
| Colour temperature (K) | 3000 |
| Voltage (V) | 230 |
| Diameter (mm) | 15 |
| CRI | 80 |
| Lamp | HITTCCE |

Accessories

| | |
|------------|----------------------------|
| 20/6604/21 | For ref: 6604/20, 6604/60. |
|------------|----------------------------|