



Dimensions

Product dimensions (mm)	ø250
Packing dimensions (mm)	245 x 245 x 245
Net weight (g)	2900
Gross weight (Kg)	3,2

Scheme

Scheme



Product

Real power (W)	Max. 60
IP	65
IK	8
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey
Energy efficiency class	D

Control gear

Control gear included	Yes
Control gear	Without Gear

Light source

Light source included	Yes
Light source	Halogen or retrofit equivalent
Lamp holder	G9
Nominal power (W)	60
Nominal luminous flux (Lm)	980
Average life time (h)	2000
Colour temperature (K)	3000
Voltage (V)	230
Diameter (mm)	14
CRI	80
Lamp	QT14

Accessories

20/6604/21	For ref: 6604/20, 6604/60.
------------	----------------------------

Architectural luminaire from the TROLL family Riddle S.

DESCRIPTION

Architectural luminaire from the TROLL family Riddle S optimised to be used as lighting outdoor areas such as public squares, parks, gardens or outdoor areas of sport buildings. Designed for wall or ceiling surface mounted as well as hanging. Luminaire body built in die-cast aluminium finished in grey. Luminaire Built-in a matt diffuser with an angle beam of floor washer. Use QT14 of Max. 60 W lightsource. Lamp not included. Luminaire Built in a ON/OFF fed at 220-240V; 50/60 Hz.

Item code	6604/60/21
Product type	OUT
Category	Surface
Family	Riddle
Subfamily	Riddle S
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a matt diffuser.
Installation instructions	Luminaire designed for wall or ceiling surface mounted as well as hanging.