




Dimensions

Product dimensions (mm)	240 x 40 x 21
-------------------------	---------------

Scheme

Scheme



Product

Real power (W)	60
Life time (h)	50000
IP	67
Electrical class insulation	Class 2
Operating temperature	From -40 °C to 50 °C.
Electrical feeding	100..277V, 50/60Hz
Colour	White

Control gear

Factor de potencia	0,95
--------------------	------

60W Power supply driver IP67 from the Troll family Standard DriverP.

DESCRIPTION

60W Power supply driver IP67 from the Troll family Standard DriverP. Driver provides constant output voltage at 24V. Small format Driver with high efficiency and low losses set with connection cable (500mm approx.) and Polarity identifiers Secondary + Red/- Black. It is protected against overload and over-temperature. Disconnection by short-circuit with automatic switching. Driver accomplish with Class C from minimum to maximum load range according to EN 61000-3-2. Driver suitable for escape lighting systems according to EN 50172. In addition driver accomplish with norms: EN55015; EN 60598-1; EN 60598-2-22; EN 61000_3-3; EN 61347-2-13; EN 61547; EN62384 & EN62493. Fed at 120-277V; 50/60Hz.

Item code	71/LDT06024
Product type	CONTROL
Category	Power supply
Family	Standard
Subfamily	DriverP
Materials	Driver encapsulated in metal box.