


Dimensions

| | |
|-------------------------|----------------|
| Product dimensions (mm) | 596 x 596 x 57 |
| Packing dimensions (mm) | 610 x 610 x 80 |
| Net weight (g) | 2799 |
| Gross weight (Kg) | 3,4 |

Scheme

Scheme




Low profile luminaire for versatile installation on ceilings from the TROLL family Perfilería LED.

DESCRIPTION

Low profile luminaire for versatile installation on ceilings from the TROLL family Perfilería LED setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general lighting of offices, schools, commercial areas or architectural spaces. Designed for ceiling recessed installation. Luminaire body made from stainless steel sheet finished in white. Luminaire built-in a prismatic diffuser with an angle beam of 100°. Luminaire sets a 45 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 3720 Lm, with an efficiency of 88,6 Lm/W and a total consumption of 42 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|---|
| Item code | 73L2/4883/33 |
| Product type | IN |
| Category | Recessed Luminaires |
| Family | Ledlouver |
| Subfamily | Profile Led |
| Materials | Luminaire body made from stainless steel sheet. |
| Optical system | Luminaire built-in a prismatic diffuser. |
| Installation instructions | Luminaire designed for ceiling recessed installation. |

Pictograms


Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 42 |
| Real luminous flux (Lm) | 3720 |
| Luminous efficiency (Lm/W) | 88,6 |
| Beam angle (°) | 100 |
| Life time (h) | 50000 |
| IP | 44/20 |
| Electrical class insulation | Class 2 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | White |
| Energy efficiency class | A+ |
| Diffuser | Prismatic diffuser |

Control gear


| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |
| Factor de potencia | 0,98 |

Light source

| | |
|----------------------------|------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 40 |
| Nominal luminous flux (Lm) | 4960 |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | 3 |
| CRI | 80 |

Photometry

Photometry



Accessories

007/12060

Adapter frame to install visible profile luminaire to a smooth non-modular. Drill 1210x610.

Picture

