




#### Dimensions

Product dimensions (mm)	120 x 203
Packing dimensions (mm)	170 x 125 x 172
Net weight (g)	620
Gross weight (Kg)	0,67

#### Scheme

Scheme




## Compact asymmetrical LED projector from the TROLL family S.D.I.V..

### DESCRIPTION

Compact asymmetrical LED projector from the TROLL family S.D.I.V. setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to light vertical planes in ephemeral installations such as stands and exhibitions, as well as fix installations like commercial shelves, libraries art galleries or similar. Designed for Installation on the TROLL triphasic track. Head built in die-cast aluminium with matt protection glass and steel rod finished in grey. Luminaire built-in a high purity wallwasher reflector with an angle beam of 85°/70°. Luminaire sets a 13 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 13 SDCM. Luminaire sets a ball joint system which allows tilting 45°. Fixture has a luminous flux of 700 Lm, with an efficiency of 53,8 Lm/W and a total consumption of 13 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire fed at 220-240V; 50/60 Hz.

Item code	747L/E83/21
Product type	IN
Category	Tracklights
Family	S.D.I.V.
Subfamily	S.D.I.V.
Materials	Head built in die-cast aluminium with matt protection glass and steel rod.
Optical system	Luminaire built-in a high purity wallwasher reflector.
Installation instructions	Luminaire designed for Installation on the TROLL triphasic track.

### Pictograms



### Product

Real power (W)	13
Real luminous flux (Lm)	700
Luminous efficiency (Lm/W)	53,8
Beam angle (°)	85 / 70
Life time (h)	50000
IP	20
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey
Energy efficiency class	A

### Control gear

Control gear	Without Gear
--------------	--------------

### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	12
Nominal luminous flux (Lm)	1200
Colour temperature (K)	3000
CRI	80

### Photometry

Photometry

