



Dimensions

| | |
|-------------------------|-----------------|
| Product dimensions (mm) | ø140 x 254 |
| Packing dimensions (mm) | 195 x 340 x 160 |
| Net weight (g) | 1365 |
| Gross weight (Kg) | 1,559 |

Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 41,5 |
| Real luminous flux (Lm) | 3971 |
| Luminous efficiency (Lm/W) | 95,7 |
| Beam angle (°) | 40 |
| Life time (h) | 50000 |
| IP | 20 |
| Electrical class insulation | Class 1 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | White |
| Energy efficiency class | A+ |

Control gear


| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |
| Factor de potencia | 0,98 |

Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 37 |
| Nominal luminous flux (Lm) | 5100 |
| Average life time (h) | 50000 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | 3 |
| CRI | 80 |

Photometry

Photometry



Accessories

2427/33

Surface base for spotlights with three-phase adapter.


Cylindrical spotlight from the TROLL family Spoty.

DESCRIPTION

Cylindrical spotlight from the TROLL family Spoty setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for installation on the TROLL triphasic track. Luminaire body built in extruded aluminium finished in white. Luminaire built-in a reflector made of high purity aluminium with an angle beam of 40°. Luminaire sets a 38 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SDCM. Luminaire sets a ball joint system which allows rotation 360° and tilting 90°. Fixture has a luminous flux of 3971 Lm, with an efficiency of 95,7 Lm/W and a total consumption of 41,5 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|---|
| Item code | 799L/M8440/33 |
| Product type | IN |
| Category | Tracklights |
| Family | Spoty |
| Subfamily | Spoty |
| Materials | Luminaire body built in extruded aluminium. |
| Optical system | Luminaire built-in a reflector made of high purity aluminium. |
| Installation instructions | Luminaire designed for installation on the TROLL triphasic track. |

Pictograms



Picture



Scheme

