




#### Dimensions

Product dimensions (mm) 20 x 1210 x 15,7

#### Scheme

Scheme



#### Product

Real power (W)	19,8
Real luminous flux (Lm)	1186
Luminous efficiency (Lm/W)	60
Beam angle (°)	60
Life time (h)	50000
IP	20
Electrical class insulation	Class 3
Photobiological risk	0 - Exempt
Operating temperature	from -20°C to 35°C
Electrical feeding	24 VDC

#### Control gear


Control gear Electronic Control Gear

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	18
Colour temperature (K)	6500
CRI	80

#### Photometry

Photometry



#### Accessories

11.7890.0001.00	Covers (Recessed, surface, 45 degrees)
11.7890.0002.00	Covers (Recessed, surface, 45 degrees)
11.7890.0011.20	1 m length recessed profile set. Includes: Recessed anodized aluminium profile (Alu6063-T5) + PC clear diffuser + Installation clips + End caps.


### Small format LED linear luminaire from the TROLL family PerfileLED.

#### DESCRIPTION

Small format LED linear luminaire from the TROLL family PerfileLED setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 6500° (cold white) optimised to be used as indoor or outdoor lighting where environmental integration was a relevant requirement such as bathrooms, kitchen furniture, shelves or retro-illumination. Designed for wall or ceiling surface mounted. Body profile built in extruded aluminium with IP65 connectors finished in grey. Luminaire built-in an optical system based on a lens made of synthetic material with an angle beam of 60°. Luminaire sets a 18 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 1186 Lm, with an efficiency of 60 Lm/W and a total consumption of 19,8 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire is fed at 220-240V; 50/60 Hz. and needs a constant power auxiliary gear.

Item code	LD033512114021
Product type	IN
Category	Surface Linears
Family	Led Profile
Subfamily	Perfiled
Materials	Body profile built in extruded aluminium with IP65 connectors.
Optical system	Luminaire built-in an optical system based on a lens made of synthetic material.
Installation instructions	Luminaire designed for wall or ceiling surface mounted.
Pictograms	


## Scheme



11.7890.0012.20

**2 m length recessed profile set. Includes:**  
**Anodized aluminium profile (Alu6063-T5)**  
**+ PC clear diffuser + Installation clips +**  
**End caps**


## Scheme



11.7890.0021.20

**1 m length surface profile set. Includes:**  
**Anodized aluminium profile (Alu6063-T5)**  
**+ PC clear diffuser + Installation clips +**  
**End caps.**


## Scheme



11.7890.0022.20

**2 m length surface profile set. Includes:**  
**Anodized aluminium profile (Alu6063-T5)**  
**+ PC clear diffuser + Installation clips +**  
**End caps.**

## Scheme



11.7890.0031.00

Aluminium profile 45 degrees profile

11.7890.0032.00

Aluminium profile 45 degrees profile

11.7890.0100.20

End covers End covers surface profile (2 units)


11.7890.0200.00

Installation staples Installation staples (1 unit)

478/33

Upper fastening staples. (1 unit)

## Scheme



478/C100/00

Transparent cover.

Scheme



478/C200/00

Transparent cover.

Scheme



478/P100/21

Aluminium profile.

Scheme



478/P200/21

Aluminium profile.


Scheme



478/T/21

Profile covers. (2 units)

Scheme



48/04

With terminals up to 4 mm<sup>2</sup> section. To join 5 mm<sup>2</sup> silicone cable to 13 mm<sup>2</sup>.

Picture




71/LD10024

96W Power supply driver from the Troll family Standard DriverP.

Picture



Scheme



71/LD15024

150W - Power supply 120-240Vac/24V.

Picture




71/LD3524

35W Power supply driver from the Troll family Standard DriverP.

Picture



Scheme




71/LD6024 60W Power supply driver from the Trollfamily Standard DriverP.

Picture



Scheme



73/DLP

Light dimming controller 12-24V. On/Off  
Push, Dali, 0-10V, 1-10V. (Master)

Picture



73/DLS


Light dimming controller 12-24V. On/Off  
Push, Dali, 0-10V, 1-10V. (Slave)

Picture

LD04400000001 30 cm cable with Female power supply  
connector.LD04400000002 30 cm cable with Male power supply  
connector.LD04400000003 30 cm interconnection cable with Male -  
Female.

LD044000000041 2 fixing plates.


Scheme



LD044000000042

15° - 2 fixing plates.


Scheme



LD04400000043

30° - 2 fixing plates.

Scheme



LD04400000044

45° - 2 fixing plates.

Scheme

