




#### Dimensions

|                         |                |
|-------------------------|----------------|
| Product dimensions (mm) | 70 x 365 x 127 |
| Net weight (g)          | 1558           |
| Gross weight (Kg)       | 1,7            |

#### Scheme

#### Scheme




## Lineal LED outdoor projector from the TROLL family Canal S.

### DESCRIPTION

Lineal LED outdoor projector from the TROLL family Canal S setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 6500° K (cold white) optimised to be used as Indoor or outdoor lighting of high heights spaces and structures. Designed for floor wall or ceiling surface mounted. Body built in extruded aluminium with frontal protection made of tempered glass finished in grey. Luminaire is IP65. Luminaire built-in an independent lens system for each led with an angle beam of 25°. Luminaire sets a 11,5 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Luminaire sets a ball joint system which allows tilting 180°. Fixture has a luminous flux of 620 Lm, with an efficiency of 53,9 Lm/W and a total consumption of 11,5 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

|                           |  |
|---------------------------|--|
| Item code                 | LD139503604000   |
| Product type              | OUT  |
| Category                  | Projectors   |
| Family                    | Canal  |
| Subfamily                 | Canal S  |
| Materials                 | Body built in extruded aluminium with frontal protection made of tempered glass. |
| Optical system            | Luminaire built-in an independent lens system for each led.                      |
| Installation instructions | Luminaire designed for floor wall or ceiling surface mounted.                    |
| Pictograms                |  |



### Product

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 11,5               |
| Real luminous flux (Lm)     | 620                |
| Luminous efficiency (Lm/W)  | 53,9               |
| Beam angle (°)              | 25                 |
| Life time (h)               | 50000              |
| IP                          | 65                 |
| IK                          | 8                  |
| Electrical class insulation | Class 1            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | Grey               |
| Energy efficiency class     | A                  |

### Control gear

|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |
| Factor de potencia    | 0,9                     |

### Light source

|                            |      |
|----------------------------|------|
| Light source included      | Yes  |
| Light source               | Led  |
| Nominal power (W)          | 10,3 |
| Nominal luminous flux (Lm) | 713  |
| Colour temperature (K)     | 6500 |
| Colour consistency (SDCM)  | 3    |
| CRI                        | 80   |

### Photometry

Photometry

